

## TECHNICAL SPECIFICATION

### BRUSHED

It is a calendered PVC film POLYMERIC with special texture, available in black and graphite color. Paper liner coated siliconized and repositionable acrylic adhesive.

- Indication:** Designed for protection and customization of vehicles, can be used for clipping. Good stability on smooth surfaces and curves, resistant to light impacts.
- Physical Property:** Front: PVC compounder 100µm (microns).  
Liner: Coated Siliconized paper 150 g/m<sup>2</sup>.  
Adhesive: acrylic repositinable 17 g/m<sup>2</sup> ( $\pm$  2g/m<sup>2</sup>).
- Supply and Durability:**
- Material packed in box and cardboard reels with a width of 1.38m.
  - Expected durability: five years (Exception: graphite – six months). In horizontal this durability is reduced to 30%. Important: durability can be extended or decreased as a result of application techniques and conservation.
- Storage:** Store at temperatures between 20°C and 30°C, relative humidity between 40% and 50%.  
Validity: two years form the date of manufacture if packed in original packaging and in an appropriate location.
- Recomendations:**
- Apply in smooth superfice; cleaned with isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
  - Do not use in places with ripples, rough surfaces and/or porous.
  - Use of excess solvent reduces the durability of the product.
  - Install immediately after cutting.
  - Once applied to avoid aggressive products and constant friction.
- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the adhesive film for special applications, we recommend customers to conduct their own testing.
- NOTE: Ours products are not part of the production chain of auto parts construction materials.

## TECHINICAL SPECIFICATION

### DIMENSION

It is a calendered PVC film POLYMERIC textured, available in two colors: white, black and red. Paper liner coated siliconized and repositionable acrylic adhesive.

**Indication:** Designed for protection and customization of vehicles and can be used for clipping. Good stability on smooth surfaces and curves, resistant to light impacts.

**Physical Property:** Front: PVC compounder 100µm (microns).  
Liner: Coated siliconized paper 150 g/m<sup>2</sup>.  
Adhesive: acrylic repositionable 17 g/m<sup>2</sup> ( $\pm$  2 g/m<sup>2</sup>).

**Supply and**

- Material packed in box and cardboard reels with width of 1,38m.

**Durability:**

- Expected life: seven years.

Important: the durability can be extended or decreased as a result of application techniques and conservation.

**Storage:**

Store at temperatures between 20 and 30°C, relative humidity between 40% and 50%. Validity: two years from the date of manufacture if packed in original packaging and in an appropriate place.

**Recomendations:**

- Apply in smooth; flat surface previously cleaned using isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and/or porous.
- Excess solvent usage reduces the durability of the product of time.
- Install immediately after cutting.
- Once applied to avoid aggressive products and constant friction.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the adhesive film for special applications, we recommend customers to conduct their own testing.

NOTE: Ours products are not part of the production chain of auto parts and construction materials.

## TECHNICAL SPECIFICATION

### PIXEL

It is a calendered PVC film POLYMERIC with special texture, available in three colors: white, red and black. Paper liner coated siliconized and repositionable acrylic adhesive.

**Indication:** Designed for protection and customization of vehicles and can be used for clipping. Good stability on smooth surfaces and curves, resistant to light impacts.

**Physical Property:**  
Front: PVC compound 100µm (microns).  
Liner: Coated siliconized paper 150 g/m<sup>2</sup>.  
Adhesive: acrylic repositionable 17 g/m<sup>2</sup> (± 2 g/m<sup>2</sup>).

**Supply and**

- Material packed in box and cardboard reels with width of 1.38m.

**Durability:**

- Expected durability: five years.  
Important: the durability can be extended or decreased as a result of application techniques and conservation.

**Storage:**

Store at temperatures between 20 and 30°C, relative humidity between 40% and 50%. Validity: two years from the date of manufacture if packed in original packaging and in an appropriate place.

**Recomendations:**

- Apply in smooth; flat surface previously cleaned using isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and/or porous.
- Excess solvent usage reduces the durability of the product of time.
- Install immediately after cutting.
- Once applied to avoid aggressive products and constant friction.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the adhesive film for special applications, we recommend customers to conduct their own testing.

NOTE: Ours products are not part of the production chain of auto parts and construction materials.

## TECHNICAL SPECIFICATION

### IMPACT BLACK

It is a calendered PVC film POLYMERIC with special texture, available the black color. Paper liner coated siliconized and repositionable acrylic adhesive.

**Indication:** Designed for protection and customization of vehicles and can be used for clipping. Good stability on smooth surfaces and curves, resistant to light impacts.

**Physical Property:** Front: PVC compounder 140µm (microns).  
Liner: coated siliconized paper 120 g/m<sup>2</sup>.  
Adhesive: acrylic repositionable 17 g/m<sup>2</sup> (± 2 g/m<sup>2</sup>).

**Supply and**

- Material packed in box and cardboard reels with width of 1.22m.

**Durability:**

- Expected durability: five years. In horizontal this durability is reduced to 30%.  
Important: the durability can be extended or decreased as a result of application techniques and conservation.

**Storage:**

Store at temperatures between 20°C and 30°C, relative humidity between 40% and 50%.  
Validity: two years from the date of manufacture if packed in original packaging and in an appropriate place.

**Recommendations:**

- Apply in smooth superficie; cleaned with isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and/or porous.
- Excess solvent usage reduces the durability of the product of time.
- Install immediately after cutting.
- Once applied to avoid aggressive products and constant friction.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the adhesive film for special applications, we recommend customers to conduct their own testing.

NOTE: Ours products are not part of the production chain of auto parts and construction materials.

## TECHNICAL SPECIFICATION

### DEEP

It is a calendered PVC film POLYMERIC with special texture available in black color. Paper liner coated siliconized and repositionable acrylic adhesive.

**Indication:** Designed for protection and customization of vehicles, can be used for clipping. Good stability on smooth surfaces and curves, resistant to light impacts.

**Physical Property:** Front: PVC compounder 150µm (microns).  
Liner: Coated siliconized paper 150 g/m<sup>2</sup>.  
Adhesive: acrylic repositionable 17 g/m<sup>2</sup> (± 2g/m<sup>2</sup>).

**Supply and**

- Material packed in box and cardboard reels with a width of 1.38m.

**Durability:**

- Expected durability: five years. In horizontal this durability is reduced to 30%.  
Important: durability can be extended or decreased as a result of application techniques and conservation.

**Storage:**

Store at temperatures between 20°C and 30°C, relative humidity between 40% and 50%.  
Validity: two years from the date manufacture if packed in original packaging and in an appropriate place.

**Recommendations:**

- Apply in smooth; flat surface previously cleaned using isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and/or porous
- Excess solvent usage reduces the durability of the product of time.
- Install immediately after cutting.
- Once applied to avoid aggressive products and constant friction.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the adhesive film for special applications, we recommend customers to conduct their own testing.  
Note: Our products are not part of the production chain of auto parts and building materials.

## TECHNICAL SPECIFICATION

### ORION

It is a calendered PVC film POLYMERIC with special texture available in black color. Paper liner coated siliconized and repositionable acrylic adhesive.

**Indication:** Designed for protection and customization of vehicles, can be used for clipping. Good stability on smooth surfaces and curves, resistant to light impacts.

**Physical Property:** Front: PVC compounder 100µm (microns).  
Liner: Coated siliconized paper 150 g/m<sup>2</sup>.  
Adhesive: acrylic repositionable 17 g/m<sup>2</sup> (± 2g/m<sup>2</sup>).

**Supply and**

- Material packed in box and cardboard reels with a width of 1.38m.

**Durability:**

- Expected durability: five years. In horizontal this durability is reduced to 30%.  
Important: durability can be extended or decreased as a result of application techniques and conservation.

**Storage:**

Store at temperatures between 20°C and 30°C, relative humidity between 40% and 50%.  
Validity: two years from the date manufacture if packed in original packaging and in an appropriate place.

**Recommendations:**

- Apply in smooth; flat surface previously cleaned using isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and/or porous
- Excess solvent usage reduces the durability of the product of time.
- Install immediately after cutting.
- Once applied to avoid aggressive products and constant friction.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the adhesive film for special applications, we recommend customers to conduct their own testing.  
Note: Our products are not part of the production chain of auto parts and building materials.