

TECHNICAL SPECIFICATION

PREMIUM

It is a calendered PVC film POLYMERIC with high gloss available in various shades, liner siliconized coated and permanent acrylic adhesive.

Indication: General use as signage, advertising, design, decoration.

Physical Property: Front: PVC calendered 80µm (microns).
Liner: coated siliconized paper 120 g/m².
Adhesive: Acrylic Permanent 20 g/m² (± 2 g/m²).

Supply and • Material packed in cardboard boxes and coils with widths of 0.61 and 1.22m.

Durability: • Expected durability: five years (except the colors Silver and Gold – six months).
Important: Durability can be extended or decreased as a result of application techniques and conservation.

Storage: Store at temperatures between 20°C and 30 °C, relative humidity between 40% and 50%.
Validity: two years from the date of manufacture if packed in original packaging and in an appropriate location.

Recommendations:

- Apply in smooth; flat surface previously cleaned using isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and/or porous.
- Excess solvent usage reduces the durability of the product of time.
- Install immediately after cutting.
- Once applied to avoid aggressive products and constant friction.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the adhesive film for special applications, we recommend customers to conduct their own testing.

Note: our products are not part of the production chain of auto parts and building materials.

TECHNICAL SPECIFICATION

SATIN PREMIUM

It is a calendered PVC film POLYMERIC of satiny appearance, available in black color, liner siliconized adhesive and permanent acrylic coated paper.

Indication: General use as signage, advertising, design, decoration.

Physical Property: Front: PVC calendered 80µm (microns).
Liner: coated paper siliconized 120 g/m².
Adhesive: Acrylic Permanent 20 g/m² (± 2 g/m²).

Supply and

- Material packed in cardboard boxes and coils with widths of 0.61 and 1.22m.

Durability:

- Expected durability: Five years (Except silver and gold: six month).
Important: the durability can be extended or decreased as a result of application techniques and conservation.

Storage:

Store at temperatures between 20 and 30°C, relative humidity between 40% and 50%. Validity: two years starting from manufacturing date, provided it is in original packaging and appropriate location.

Recommendations:

- Apply in smooth; flat surface previously cleaned using isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and / or porous
- Excess solvent usage reduces the durability of the product of time.
- Install immediately after cutting.
- Once applied avoid aggressive products and constant friction.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the adhesive film for special applications, we recommend customers to conduct their own testing.