

## TECHNICAL SPECIFICATION

### ULTRA

It is a calendered PVC film POLYMERIC with high brightness, available in solid and metallic colors. Paper liner coated siliconized and repositionable acrylic adhesive.

**Indication:** Designed for protection and customization of vehicles and can be used for clipping. Good stability on smooth surfaces and curves, resistant to light impacts.

**Physical Property:** Front: polymeric calendered PVC 100µm (microns).  
Liner: Paper coated siliconized 150 g/m<sup>2</sup>.  
Adhesive: acrylic repositionable 17 g/m<sup>2</sup> ( $\pm$  2 g/m<sup>2</sup>).

**Supply and**

- Material packed in box and cardboard reels with width of 1.38m.

**Durability:**

- Expected durability: five years (Exceptions: metallic colors – one year). In horizontal this durability is reduced to 30%.

Important: the durability can be extended or decreased as a result of application techniques and conservation.

**Storage:**

Store at temperatures between 20°C and 30°C, relative humidity between 40% and 50%.

Validity: two years from the date of manufacture if packed in original packaging and in an appropriate place.

**Recomendations:**

- Apply in smooth surface; cleaned with isopropyl alcohol avoiding contact with impurities, oils or any other chemical.
- Do not use in places with ripples, rough surfaces and/or porous.
- Excess solvent usage reduces the durability of the product of time.
- Install immediately after cutting.
- Once applied to avoid aggressive products and constant friction.

- The above data are based on laboratory tests that Alltak believes to be reliable and are provided for informational purposes only and do not constitute any form of guarantee.
- Due to diversity of potential influencing factors during application and use of the adhesive film for special applications, we recommend customers to conduct their own testing.

NOTE: Ours products are not part of the production chain of auto parts and construction materials.